

Forget all you have seen in coffee vending...

Coffeemar 250



Technical features

Functional characteristics:

- Two different cup-dispensing models depending on cup diameter: 65 to 67mm. and 67 to 69mm
- Stir-stick dispenser can be adjusted for lengths between 75mm. and 115mm.
- Self-cleaning mixing circuit, product delivery and grinding assembly: Manual or automatic (programmable).
- Steam-proof sugar addition straight into the cup.
- Constant boiler water temperature control.
- Presure valve for a constant presure on the entire brewing cycle.
- Self adjusting grinding group for a prefect thickness of the coffee.

Construction:

- Steel with rust-proof treatment and vandal-proof lock with crowbar-resistant door integrated into the cabinet.
- Height x Width x Depth: 59" x 19.5" x 22"

Programming:

- On-site general programming using the machine's keypad, by hand-held terminal Jofemar EasyFlash, direct connection for PC computer or Telemetry Modem using Jofemar software Vending Track.
- Parameters of doses programing visualized on grams.
- Complete accounting data storage and reporting.
- Four different programming access levels: Operator, Technician, Maintenance and Master.

Optional Kits:

- Water self-feeding kit (One or two 25-litre
- Water filters: water softener or flavour filter.



Wippers and bean brewer



Product collection area



Capacity for 340 8oz cup







The only machine that extract all the coffee essence.

The Coffeemar bean-to-cup brewer is the first and the only one in the market to incorporate a pressured valve, ensuring the whole coffee brewing cycle is done with the perfect water pressure, even at the start, getting out from the first to the last water drop all the essence and flavor of the coffee.

As well as this advance, Jofemar has introduced other innovations such an automatic regulation on the coffee grinding; by constantly measuring the pressure, the machine mechanically adjusts the grinder overture for a perfect thickness into the coffee brewer.

With the model G250 Jofemar covers its expectancy on always offering the best coffee quality even for small locations, a machine which its dimensions and outer design makes it perfect for any surrounding.

Coffeemar G250	
Lightened Panel	10" x 9.5"
Graphic display	3.6" x 21/4"
Dimmensions	59" x 19.5" x 22"
Weight	221 Lbs.
Water Supply	1/4" (Minimun-Maximun: 05-10 bar).
Power Supply	110V, 60Hz (Optional 220V)
Max. Power	1.100 watts.
Consumption	3,09 kwh/24 hours Stand By.



